

MODEL: APS9 BODY CAMERA (ANDROID OS)



▶ SYSTEM

SOC Chip	8-core 64-bit 2.0G CPU
Operating System	Android 12
RAM	2GB
ROM	16GB

▶ CAMERA

Camera Quantity	1*Front camera + 1*Rear camera
Camera Lens	Scratch-resistant
Image Resolution	Maximum support 54M
Image Format	JPEG
Front Camera	-Megapixel
Rear Camera	-Megapixel

▶ VIDEO

Compression	H.264
Video Resolution	2K (2560*1440P), 1920*1080P, 1280*720P, 720*480P
Video Format	MP4
Dual-stream	Support
Display Screen	2.8 inches 480*640 Capacitive multi-touchscreen
One-touch Recording	Support
Video Input	Support external 1080P USB camera


AUDIO

Microphone	Built-in Dual high-quality microphones
Audio Format	AAC
Speaker	Built-in 2W speaker


NETWORK

Frequency Band	GSM: B2, 3, 5, 8 WCDMA: B1, 5, 8 FDD-LTE: B1, 2, 3, 4, 5, 7, 8, 20, 28A/B TDD-LTE: B38, 39, 40, 41
GPS	Built-in, GPS, BDS, GLONASS, Galileo
Bluetooth	BT5.0
NFC	Optional (external antenna is required)
4G	Support
WiFi	Built-in, 802.11 a/b/g/n/ac, 2.4G+5GHz


LIGHT

Night Vision	Support, 1*White light, 4*IR lights
White Balance	Auto white balance
Laser Light	Support


INTERFACE

Shortcut Button	Power, Video, Audio, Photo, SOS, PTT, Tag, FN
Sim-card Slot	Built-in 1*Nano-Sim card slot
USB Interface	1*Type-C + 1*Micro USB2.0
USB Interface Function	<ol style="list-style-type: none"> Charging OTG devices (including USB cameras) Software Upgrade / Copy Data



BATTERY

Type	Removable
Capacity	3050mAh replaceable battery, supports 11 hours of continuous video recording
Charging Time	Less than 3 hours
Charging Cycle	500 times
Continuous Electricity System	Built-in 60mAh small battery, supports battery replacement and continuous power



GENERAL

Storage Capacity	TF-Card / 32GB (scalable to 256GB)
Watermark	OSD
Ingress Protection	IP66
Shock Resistance	2 Meters
Weight	166g(without clip)
Dimensions	93mm*70mm*26mm
SOS Alarm	Support
SOS Alarm	Support
G/M-Sensor	Built-in
Vibration Motor	Built-in
Digital Zoom	Maximum support 24X digital zoom
Pre and Post-recording	30S
Pre and Post-recording	30S
Playback	Support
Voice Broadcast	Support TTS voice broadcast
Motion Detection	Support
Face & License Plate Recognition	Optional
Voice Intercom	Support group intercom and end-to-end intercom
Language	English
Operating Temperature	-20°C ~ 55°C
Storage Temperature	-20°C ~ 60°C
Operating Relative Humidity	40% ~ 80%
Storage Relative Humidity	63% (30°C)